
# Product data sheet Characteristics

# MTN632760 KNX ARGUS 180/2.20 m flush-mounted, aluminium, System M



#### Main

IVIAIII		
Range of product	KNX	
Aesthetic name	M-Arc	
	M-Elegance	
	M-Plan	
	M-Plan glass	
	M-Smart	
	M-Star	
	System M	
Product or component type	Movement sensor	
Bus type	KNX	
Number of channels	5	
Colour tint	Aluminium	

## Complementary

		<del>-</del>
Type of setting	Light sensitivity adjustable	<u>e</u> <u>e</u>
Wiring device mounting	Flush	100
Mounting height	2.5 m	. <u>.</u> .
Duty cycle	15300 minutes	
Time delay	1 second switch-on	Stirit
Movement detection area	16 m	
Horizontal detection angle	0180 °	, s
Detection face	Lateral 8 m	
Protection type	Creep zone protection	2. 5
Material	Plastic matt	
Surface treatment	Varnished	
		<u> </u>

### **Environment**

Environmental health and issues	Halogen free	
	_	

#### Offer Sustainability

Sustainable offer status	Not Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1342 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Contractual warranty		

Contractual warranty			
Warranty period	18 months		