Product data sheet Characteristics

MTN6180-0460

KNX Push-button Pro, aluminium, System M



| Main | | |
|---------------------------|-----------------|--------------|
| Range of product | KNX | <u></u> |
| Aesthetic name | M-Arc | ō \$ |
| | M-Elegance | <u> </u> |
| | M-Plan | <u> </u> |
| | M-Plan glass | |
| | M-Smart | |
| | M-Star | - |
| | System M | <u>.</u> |
| Product or component type | Push-button pro | <u>.</u> |
| Bus type | KNX | |
| Number of FUNCTION keys | 4 | |
| Colour tint | Aluminium | |
| | | ÷ |

Complementary

| Control type | Proximity function | |
|------------------------|--|--|
| Device mounting | Flush | |
| Wiring device mounting | Flush | |
| Function available | Pulse edges trigger 1-, 2-, 4- or 8-bit telegrams Pulse edges with 2-byte telegrams 8-bit linear regulator Scene retrieval Scene saving Push-button with 1 to 4 operating buttons With status displays Backlit symbols Behaviour and brightness of the status displays Night mode: LEDs light up with reduced brightness Express setting: Calls up a pre-set configuration Advanced setting: Individual configuration Switching, toggling, dimming (single/dual-surface) | |
| | Blind (single/dual-surface) Disable functions Programmable with ETS4 and higher Dismantling protection with accesories | e de la companya de l |
| Local signalling | LED | |

| Material | Plastic matt |
|-------------------|--------------|
| Surface treatment | Varnished |

Environment

| IP degree of protection | IP20 |
|---------------------------------|--------------|
| Environmental health and issues | Halogen free |