



Main

Aesthetic name	Unica KNX
Product or component type	Switch
Device presentation	Mechanism
Switch function	2-way
Transmission support medium	Infrared
Rated current	10 A, 250 V AC, 50/60 Hz
Actuator	Push-button
Number of modules	2 modules
Fixing mode	Screws
Cover plate colour tint	Ivory

Complementary

Contacts type and composition	2 NO
Opening distance	> 3 mm
Pilot light	Blue LED : 1 mA (temperature : 15 °C)
Connections - terminals	Screwless terminals
Cable cross section	<= 2.5 mm ² (flexible) <= 2.5 mm ² (rigid)
Insulation resistance	> 5 MOhm @500 V
Dielectric strength	> 2000 V
Standards	EMC directive LV directive
Ambient air temperature for operation	-5...45 °C



Environment

IK degree of protection	IK01
IP degree of protection	IP20
Environmental characteristic	Acetone

Alcohol
Ammonia
Bleach
Liquid soap
Oil
Petrol
UV resistant
Window-cleaning fluid

Environmental health and issues	Halogen free
---------------------------------	--------------

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will be compliant on 4Q2019 Will be compliant on 4Q2019
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available  Product environmental
Product end of life instructions	Need no specific recycling operations  End of life manual

Contractual warranty

Warranty period	18 months
-----------------	-----------
