Product data sheet Characteristics

MTN617219

Push-button, 2-gang plus, polar white, glossy, System M





Main

Main.		
Main Range of product	KNX	
Aesthetic name	M-Star	
Aestretic name	M-Arc	
	M-Plan glass	
	System M	
	M-Elegance M-Plan	
	M-Smart	
Product or component type	Push-button	
Bus type	KNX	
Number of FUNCTION keys	4	
Colour tint	Polar white glossy	
Colour code	RAL 9010	
Complementary		
	Flush	
Device mounting	Flush Flush	
Device mounting Wiring device mounting		
Device mounting Wiring device mounting Local signalling	Flush	
Device mounting Wiring device mounting	Flush LED	
Device mounting Wiring device mounting Local signalling Marking location	Flush LED Marking on legend holder	
Device mounting Wiring device mounting Local signalling Marking location Material	Flush LED Marking on legend holder	
Device mounting Wiring device mounting Local signalling Marking location Material Environment	Flush LED Marking on legend holder	
	Flush LED Marking on legend holder Plastic brilliant	
Device mounting Wiring device mounting Local signalling Marking location Material Environment IP degree of protection Environmental health and issues	Flush LED Marking on legend holder Plastic brilliant	
Device mounting Wiring device mounting Local signalling Marking location Material Environment IP degree of protection	Flush LED Marking on legend holder Plastic brilliant	

Complementary

Device mounting	Flush	
Wiring device mounting	Flush	3
Local signalling	LED	
Marking location	Marking on legend holder	
Material	Plastic brilliant	

Environment

IP degree of protection	IP20	
Environmental health and issues	Halogen free	<u></u> ن

Offer Sustainability

Sustainable offer status	Green Premium product	. T
RoHS (date code: YYWW)	Compliant - since 0803 - Schneider Electric declaration of conformity	aimer

	Schneider Electric declaration of conformity	
REACh	Reference contains SVHC above the threshold - Go to CaP for more details	
	Go to CaP for more details	
Product environmental profile	Available	
	Product environmental	
Product end of life instructions	Available	
	End of life manual	
Contractual warranty		
Warranty period	18 months	